

HD 1110

PLASTIC HORN SPEAKER WITH DRIVER

DESCRIPTION

Extremely compact horn speaker with high acoustic output. The HD 1110 is particularly suitable for use in call or alarm systems in places with a high level of background noise. Fully protected against atmospheric agents, it can also be used outdoors.



FEATURES

- Body in RAL 7035 grey plastic.
- Solid, compact construction
- Attachment bracket supplied
- Driver impedance 8 Ohm

Rev. G Last update: 02/08/2022



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB):	900 Hz ÷ 13000 Hz
	Max SPL @ 1m:	114 dB
	Coverage angle:	175°
	System Sensitivity:	101 dB
Power section	Nominal Impedance:	8 ohm
	Power Handling:	20 W
	Peak Power Handling:	80 W PEAK
	Recommended Amplifier:	40 W
Transducers	Compression Driver:	1 x 1.5"
Input/Output section	Input connectors:	Cable
	Output connectors:	Cable
Standard compliance	CE compliance:	Yes
Physical specifications	Cabinet/Case Material:	Plastic
	Hardware:	U bracket
Size	Depth:	93 mm / 3.66 inches
	Diameter:	100 mm / 3.94 inches
	Weight:	0.42 kg / 0.93 lbs
Shipping informations	Package Height:	100 mm / 3.94 inches
	Package Width:	120 mm / 4.72 inches
	Package Depth:	120 mm / 4.72 inches
	Package Weight:	1.2 kg / 2.65 lbs

PART NUMBER

· 13133030

HD 1110

EAN 8024530010140



DRAWINGS





