

# CD240-K

## DRIVER

### DESCRIPTION

The CD240-K is a high performance 1.5-inch diaphragm compression driver with a 1.0 inch exit throat featuring a single piece, low compression, radial phase plug. The diaphragm and suspension are precision formed from Polyimide for high stability also at high working temperature. The CD240-K is a very compact size, versatile driver for professional applications.



### FEATURES

- 1.5-inch Diaphragm, 1.0-inch Exit Throat
- 50 watt Continuous program power handling
- Frequency range: 1500 Hz - 20 kHz
- Optimized geometry radial phase plug
- Very compact size for array applications
- Ceramic magnet assembly

## TECHNICAL SPECIFICATIONS

### General specifications

Exit Throat Diameter:	1.0 inch / 25 mm
Related Impedance:	8 ohm
Program Power (watt):	50 W
Power handling capacity (watt):	25 W
Sensitivity:	109 dB
Frequency range:	1500 - 20000 Hz
Diaphragm Material:	Polymide
Suspension Material:	Polymide
Suspension Design:	Radial
Minimum Impedance (ohm):	7.00 ohm
Voice Coil Diameter:	1.5 inch / 38 mm
Voice Coil Material:	Edgewound Aluminium
Voice Coil Former Design:	Straight - Kapton
Number of layers:	1
Kind of layers:	outside
Flux Density:	1.6 T
Phase Plug Design:	10 radial slots
Phase Plug Material:	PP Composite
Magnetics:	Ceramic

### Thiele - small parameters

Bl factor (Bl) (T x m):	4.00 T x m
-------------------------	------------

### Mounting informations

Overall diameter:	91 mm / 3.58 inches
Overall height:	51 mm / 2.01 inches
Mounting:	4 x 6 mm threaded holes at 90°

### Standard compliance

CE marking:	Yes
-------------	-----

### Size

Weight:	0.93 kg / 2.05 lbs
---------	--------------------

### Shipping informations

Package Height:	85 mm / 3.35 inches
Package Width:	160 mm / 6.3 inches
Package Depth:	155 mm / 6.1 inches
Package Weight:	1.56 kg / 3.44 lbs

## PART NUMBER

- **15100014**  
CD240-K