

# LF18Y408

## WOOFER

### DESCRIPTION

Incredibly linear frequency response characteristics, the highest power handling of any comparable 18-inch neodymium transducer, the lowest power compression. The LF18Y408 uses a fibre loaded cone assembly along with a high excursion triple roll, constant geometry surround. This combination provides remarkable strength venting system guarantee a very efficient voice coil ventilation for minimum power compression and higher power handling.



### FEATURES

- 4 - inch, fiberglass inside-outside copper voice coil
- 2400 Watt continuous program power handling
- 98 dB Sensitivity
- 30 Hz - 1 kHz Frequency range
- Dual-forced air ventilation and 15mm top plate for minimum power compression
- Dual spider design with silicon based dampening control
- Triple-roll surround and corrugated straight cone geometry

## TECHNICAL SPECIFICATIONS

### General specifications

Nominal Diameter:	18 inch / 457 mm
Rated Impedance:	8 ohm
Program Power (watt):	2400 W
Power handling capacity:	1200 W
Sensitivity:	98.0 dB
Frequency range:	30 - 1000 Hz
Effective piston diameter:	395 mm / 15.55 inch
Max. Excursion Before Damage:	52 mm / 2.05 inch
Minimum Impedance (ohm):	6.3 ohm
Voice Coil Diameter:	4.0 inch / 102 mm
Voice Coil Winding Material:	Copper
Voice Coil Length:	25 mm / 0.98 inch
Number of layers:	2
Kind of layers:	inside/outside
Top Plate Thickness:	15 mm / 0.59 inch
Cone Design:	Straight
Surround Material:	Polycotton
Surround Design:	Triple roll

### Thiele - small parameters

DC resistance (Re) (ohm):	5.10 ohm
Mechanical factor:	6.50 Qms
Electrical factor:	0.27 Qes
Total factor:	0.26 Qts
Bl factor (Bl) (T x m):	27.80 T x m
Effective moving mass (Mms):	201.0 g
Equivalent Cas air loaded (Vas):	257.0 liters
Effective piston area (Sd):	0.120 m <sup>2</sup>
Max. linear excursion (Xmax):	9 mm
Voice coil inductance @ 1kHz (Le1k):	2.50 mH
Half-space efficiency (Eff):	3.01%

### Mounting informations

Overall diameter:	465 mm / 18.31 inches
Bolt circle diameter:	442-447 mm / 17.4-17.6 inch
Bolt hole diameter:	7 mm / 0.28 inch
Front mount baffle cut-out:	424 mm / 16.69 inch
Rear mount baffle cut-out:	424 mm / 16.69 inch
Volume occupied by the driver:	5.5 liters / 0.22 ft <sup>3</sup>

### Standard compliance

CE marking:	Yes
-------------	-----

### Size

Weight:	9.5 kg / 20.94 lbs
---------	--------------------

### Shipping informations

Package Height:	260 mm / 10.24 inches
Package Width:	520 mm / 20.47 inches
Package Depth:	500 mm / 19.69 inches
Package Weight:	11.4 kg / 25.13 lbs



**PART NUMBER**

- **11100126**  
LF18Y408  
8ohm



