

# **MB15Y358**

MID - BASS

#### **DESCRIPTION**

This MB15Y358 is designed to provide an excellent linearity in the frequency response with low distortion. The transducer is built around a very stronger neodymium magnetic structure and a new 3,5" voice coil, this combination provides to increase the power handling especially in comparison a standard 3" voice coil. The unique Dual-forced air venting system guarantee a very efficient voice coil ventilation for minimize the power compression at the higher power handling.



#### **FEATURES**

- 3.5-inch, inside/outside copper voice coil
- 1300W continuous program power handling
- 100 dB Sensitivity
- 40 Hz 3 kHz Frequency range
- Dual-forced air ventilation for minimum power compression
- Dual spider design with silicon based dampening control

Rev. B Last update: 08/03/2022



## **TECHNICAL SPECIFICATIONS**

TECHNICAL SPECIFICATIONS		
General specifications	Nominal Diameter:	15 inch / 381 mm
	Rated Impedance:	8 ohm
	Program Power (watt):	1300 W
	Power handling capacity:	650 W
	Sensitivity:	100.0 dB
	Frequency range:	40 - 3000 Hz
	Effective piston diameter:	330 mm / 12.99 inch
	Max. Excursion Before Damage:	39 mm / 1.54 inch
	Minimum Impedance (ohm):	6.8 ohm
	Voice Coil Diameter:	3.5 inch / 89 mm
	Voice Coil Winding Material:	Copper
	Voice Coil Length:	17 mm / 0.67 inch
	Number of layers:	2
	Kind of layers:	inside/outside
	Top Plate Thickness:	11 mm / 0.43 inch
	Cone Design:	Curved
	Surround Material:	Polycotton
	Surround Design:	M-roll
Thiele - small parameters	DC resistance (Re) (ohm):	5.60 ohm
	Mechanical factor:	4.00 Qms
	Electrical factor:	0.24 Qes
	Total factor:	0.22 Qts
	BI factor (BI) (T x m):	22.50 T x m
	Effective moving mass (Mms):	80.0 g
	Equivalent Cas air loaded (Vas):	191.0 liters
	Effective piston area (Sd):	0.090 m2
	Max. linear excursion (Xmax):	6 mm
	Voice coil inductance @ 1kHz (Le1k):	1.65 mH
	Half-space efficency (Eff):	5.68%
Mounting informations	Overall diameter:	393 mm / 15.47 inches
	Bolt circle diameter:	371-376 mm / 14.61-14.8 inch
	Bolt hole diameter:	7 mm / 0.28 inch
	Front mount baffle cut-out:	354 mm / 13.94 inch
	Rear mount baffle cut-out:	354 mm / 13.94 inch
	Volume occupied by the driver:	3.8 liters / 0.15 ft3
Standard compliance	CE marking:	Yes
Size	Weight:	5.16 kg / 11.38 lbs
Shipping informations	Package Height:	230 mm / 9.06 inches
	Package Width:	440 mm / 17.32 inches
	-	
	Package Depth: Package Weight:	440 mm / 17.32 inches 6.52 kg / 14.37 lbs



### **PART NUMBER**

· 11100129

8ohm

MB15Y358









